

Class 1 VCBC Acrylic Freestanding Baths

Product Disclosure Information Self-Assessment

Version: V070823

Product name	VCBC Acrylic Freestanding Baths
Product line	VCBC Acrylic baths are part of the VCBC range by Bath Co.
Product identifier	Curve Back-to-Wall, Curve Corner, Immerge, Relax, Harmony

Product description

VCBC freestanding baths are made from acrylic with fibreglass backing. they are supported by steel brackets and adjustable legs. The overflow and waste fittings are brass and plastic.

They have a glossy, white finish. The baths are 1500-1700 mm long, 560-800mm wide and 560-600mm high

Relevant building code clauses

- B2 Durability B2.3.1 (c)
- F2 Hazardous building materials F2.3.1

G1 Personal Hygiene - G1.3.2

G12 Water Supplies - G12.3.5

Contributions to compliance

• B2 Durability o B2.3.1 VCBC shower trays carry a 5 year domestic or 1 year non-domestic warranty.

• E3 Internal Moisture

o E3.1(b) Protect household units from damage caused by free water from another household unit in the same building o E3.3.1 An adequate combination of thermal resistance, ventilation and space temperature must be provided to all bathrooms, laundries and other spaces where moisture may be generated or may accumulate o E3.3.3 Surfaces must be impervious to water and easily cleaned o E3.3.6 Surfaces of building element likely to be splashed must be constructed in a way that prevents water splash from penetrating behind linings or into concealed spaces

• F2 Hazardous building materials o F2.3.1 VCBC shower trays are safe when handled. There are no requirements for this product in order to comply with Acceptable Solution F2/AS1, First Edition Amendment 3,

2017.

• G1 Personal Hygiene o G1.3.2 VCBC shower trays shall be installed to: facilitate sanitation, avoid harbouring dirt or germs, allow effective cleaning, discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and provide a healthy safe disposal system when non-water-borne disposal is used Sanitary fittings should be easy to locate and identify, with their operation easy to understand and suitable for both standing and seated users.

•G12 For Water supplies G12, the prime building product objective is to ensure that the product used in water supply will not contaminate potable water either by way of material leaching into the water or cross connections and will not leak

Scope of use

VCBC Acrylic free-standing baths are intended for domestic and commercial use. They are designed to enclose water. They can be used with water temperatures up to 55 degrees celsius.

VCBC Acrylic free-standing baths are to be installed using the waste fitting supplied with the bath.

These baths are to be mounted on a flat floor surface and sealed when fitted against a wall or walls.

Conditions of use

VCBC acrylic free-standing baths must be installed in accordance with the instructions provided. We recommend these baths are installed by an authorised installer. Floor surfaces must be flat and free of movement, and unheated.

This product is intended for domestic and commercial use. This product is cleanable and impervious to moisture — cleaning of the bath shall be done in accordance with the manufacturer's cleaning instructions.

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
VCBC Acrylic Baths Installation Instructions (Design, Installation)	V070823	https://www.bathco.co.nz/bathrooms/baths
VCBC Warranty (Warranty)	V070823	https://www.bathco.co.nz/warranties

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Bathroom Brands Group
Legal and trading name of importer	Bath Co.

Importer address for service	86 Wigram Road Christchurch 8025
Importer website	www.bathco.co.nz
Importer NZBN	9429041650790
Importer email	info@bathco.co.nz
Importer phone number	033430969

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

Appendix

BPIR Ready selections

Category: Sanitary fixtures and appliances [legacy category]

	Yes	No
Suitable for Accessible facilities		×
Provision of hot water	×	

Building code performance clauses

All relevant building code performance clauses listed in this document:

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- (c) 5 years if:
 - i. the *building elements* (including services, linings, renewable protective coatings, and *fixtures*) are easy to access and replace, and
 - ii. failure of those building elements to comply with the *building code* would be easily detected during normal use of the *building*.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G1 Personal Hygiene

G1.3.2

Sanitary fixtures shall be located, constructed and installed to:

- a. facilitate sanitation,
- b. avoid risk of food contamination,
- c. avoid harbouring dirt or germs,
- d. provide appropriate privacy,
- e. avoid affecting occupants of adjacent spaces from the presence of unpleasant odours, accumulation of offensive matter, or other source of annoyance,
- f. allow effective cleaning,
- g. discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and
- h. provide a healthy safe disposal system when non-water-borne disposal is used.

G12 Water Supplies

G12.3.5

Sanitary fixtures and sanitary appliances must be provided with hot water when intended to be used for

- a. utensil washing; and
- b. personal washing, showering, or bathing.