

Class 1

VCBC Stainless Laundry Sinks

Product Disclosure Information Self-Assessment

Version: V180923

Product name	VCBC Stainless Laundry Sinks
Product line	
Product identifier	4045, 5045

Product description

450 x 400 x 215mm (5045) and 350 x 400 x 215mm (4045) under-mounted laundry sink.

The Kordura laundry sinks are composed of 1.2mm 304 grade stainless steel

The laundry basins are a single basin and come with an integrated overflow and waste. This needs to be fitted in accordance with the instructions provided.

Relevant building code clauses

- B2 Durability B2.3.1 (c)
- E3 Internal moisture E3.3.2
- F2 Hazardous building materials F2.3.1
- G1 Personal Hygiene G1.3.2
- G3 Food preparation and prevention of contamination G3.3.1 (b), G3.3.2 (b)

Contributions to compliance

• B2 Durability o B2.3.1 VCBC stainless laundry basins carry a 5 year warranty for normal, domestic use, and 1 year warranty for commercial use

• E3 Internal Moisture VCBC stainless laundry basins have an integrated overflow with limited capacity. They must be fitted so that they comply with mandatory parts of the building Code of Practice involving internal wetarea waterproof membrane systems: • NZBC clause E3.3.2 when installed in a space containing sanitary fixtures or sanitary appliances, and a floor waste is included where shown by this Code of Practice: o E3.3.2 - Free water from accidental overflow from sanitary fixtures or sanitary appliances must be disposed of in a way that avoids loss of amenity or damage to household units or other property.

• F2 Hazardous building materials o F2.3.1 VCBC stainless laundry basins are safe when handled. There are no requirements for this product in order to comply with Acceptable Solution F2/AS1, First Edition Amendment 3, 2017.

• G1 Personal Hygiene o G1.3.2 VCBC stainless laundry basins shall be installed to: facilitate sanitation, avoid harbouring dirt or germs, allow effective cleaning, discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and provide a healthy safe disposal system when non-water-borne disposal is used Sanitary fittings should be easy to locate and identify, with their operation easy to understand and suitable for both standing and seated users

Scope of use

VCBC stainless laundry sinks are intended for use where an integrated waterproof membrane system has been used.

They are suitable for domestic and commercial use. They are to be undermounted only.

They are designed for areas fitted with a floor waste and integrated waterproof membrane so that accidental overflow will not cause loss of amenity or damage to household units or other property

Conditions of use

VCBC stainless laundry sinks are supplied with a waste and overflow that must be fitted in accordance with the instructions so that any overflow is contained and free from blockage.

The product must be installed by a registered plumber. The basket waste should be cleaned regularly and overflow not impeded in any way.

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
VCBC Stainless Laundry Sink Information (Design)	V180923	https://www.bathco.co.nz/laundry/laundry-sinks
VCBC Stainless Sink Warranty (Warranty)	V180923	https://www.bathco.co.nz/warranties

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Higold Industries
Legal and trading name of importer	Bath Co.

First party self-assessment generated Oct 4, 2023 with BPIR Ready. Source: https://bpir.nz/form/view?wz=6ccb612d98d9920d0b21ed08951724395a3bba72 Get BPIR Ready | bpir.nz

Importer address for service	86 Wigram Road Christchurch 8025
Importer website	www.bathco.co.nz
Importer NZBN	9429041650790
Importer email	info@bathco.co.nz
Importer phone number	033430969

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

Appendix

BPIR Ready selections

Category: Kitchen and laundry sinks

	Yes	No
Integrated overflow	×	
Suitable for accessible facilities		×

Building code performance clauses

All relevant building code performance clauses listed in this document:

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

- (c) 5 years if:
 - i. the *building elements* (including services, linings, renewable protective coatings, and *fixtures*) are easy to access and replace, and
 - ii. failure of those building elements to comply with the *building code* would be easily detected during normal use of the *building*.

E3 Internal moisture

E3.3.2

First party self-assessment generated Oct 4, 2023 with BPIR Ready. Source: <u>https://bpir.nz/form/view?wz=6ccb612d98d9920d0b21ed08951724395a3bba72</u>

Get BPIR Ready | bpir.nz

Free water from accidental overflow from *sanitary fixtures* or *sanitary appliances* must be disposed of in a way that avoids loss of *amenity* or damage to *household units* or *other property*.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G1 Personal Hygiene

G1.3.2

Sanitary fixtures shall be located, constructed and installed to:

- a. facilitate sanitation,
- b. avoid risk of food contamination,
- c. avoid harbouring dirt or germs,
- d. provide appropriate privacy,
- e. avoid affecting occupants of adjacent spaces from the presence of unpleasant odours, accumulation of offensive matter, or other source of annoyance,
- f. allow effective cleaning,
- g. discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and
- h. provide a healthy safe disposal system when non-water-borne disposal is used.

G3 Food preparation and prevention of contamination

G3.3.1

Food preparation facilities shall be hygienic and include:

(b) means for food rinsing, utensil washing and waste water disposal

G3.3.2

Spaces for food preparation and utensil washing shall have:

(b) all *building elements* constructed with materials which are free from *hazardous substances* which could cause contamination to the *building* contents