



VCBC Shower Baths

Product Disclosure Information Self-Assessment

Version: V100823

Product name	VCBC Shower Baths
Product line	Shower baths system with glass screens, side panels and wall panels
Product identifier	B Shower Bath, Square Shower Bath

Product description

VCBC Shower Baths and bath side panels are made from white acrylic and fibreglass backing to add support.

These baths are available in left or right orientations

The baths are self supporting on adjustable steel legs. the include brass and plastic overflow and waste fittings.

The wall panels are made of white acrylic sheets

The side panels are tempered glass with chrome trim

The baths are 1700mm L x 430mm H x 850-900mm W

Relevant building code clauses

B2 Durability — B2.3.1 (c)

F2 Hazardous building materials — F2.3.1

G1 Personal Hygiene — G1.3.2

G12 Water Supplies - G12.3.5

Contributions to compliance

- B2 Durability o B2.3.1 VCBC Shower Baths carry a 5 year warranty for normal, domestic use, and 1 year warranty for commercial use
- F2 Hazardous building materials o F2.3.1 VCBC Shower Baths are safe when handled. There are no

requirements for this product in order to comply with Acceptable Solution F2/AS1, First Edition Amendment 3, 2017.

- G1 Personal Hygiene o G1.3.2 VCBC Shower Baths shall be installed to: facilitate sanitation, avoid harbouring dirt or germs, allow effective cleaning, discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and provide a healthy safe disposal system when non-water-borne disposal is used Sanitary fittings should be easy to locate and identify, with their operation easy to understand and suitable for both standing and seated users.
- •G12 For Water supplies G12, the prime building product objective is to ensure that the product used in water supply will not contaminate potable water either by way of material leaching into the water or cross connections and will not leak

Scope of use

VCBC Acrylic Shower Baths are intended for domestic and commercial use. They are designed to enclose water. They can be used with water temperatures up to 55 degrees celsius.

VCBC Acrylic Shower Baths are to be installed using the waste fitting supplied with the bath.

These baths are to be mounted on a stable floor surface and sealed when fitted against the walls.

Conditions of use

VCBC acrylic Shower Baths must be installed in accordance with the instructions provided. We recommend these baths are installed by an authorised installer. Floor surfaces must be flat and free of movement, and unheated.

These products are intended for domestic and commercial use. They are cleanable and impervious to moisture — cleaning of the bath shall be done in accordance with the manufacturer's cleaning instructions.

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
VCBC Shower Baths Further Info (Design, Installation)	V100823	https://www.bathco.co.nz/bathrooms/baths/shower-baths/1/? max_price=8000&max_width=3000&ob=new&od=
Shower Baths Warranty Info (Warranty)	V100823	https://www.bathco.co.nz/warranties

Contact details

Manufacture location	Overseas	
Legal and trading name of manufacturer	Bathroom Brands Group	

Legal and trading name of importer	Bath Co.
Importer address for service	86 Wigram Road Christchurch 8025
Importer website	www.bathco.co.nz
Importer NZBN	9429041650790
Importer email	info@bathco.co.nz
Importer phone number	033430969

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

Appendix

BPIR Ready selections

Category: Sanitary fixtures and appliances [legacy category]

		163	140	
Suitable for Accessible facilities			×	Ì
	Provision of hot water	×		Ì

Building code performance clauses

All relevant building code performance clauses listed in this document:

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the specified intended life of the building, if stated, or:

- (c) 5 years if:
 - i. the *building elements* (including services, linings, renewable protective coatings, and *fixtures*) are easy to access and replace, and
 - ii. failure of those building elements to comply with the *building code* would be easily detected during normal use of the *building*.

Vac

No

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G1 Personal Hygiene

G1.3.2

Sanitary fixtures shall be located, constructed and installed to:

- a. facilitate sanitation,
- b. avoid risk of food contamination,
- c. avoid harbouring dirt or germs,
- d. provide appropriate privacy,
- e. avoid affecting occupants of adjacent spaces from the presence of unpleasant odours, accumulation of offensive matter, or other source of annoyance,
- f. allow effective cleaning,
- g. discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and
- h. provide a healthy safe disposal system when non-water-borne disposal is used.

G12 Water Supplies

G12.3.5

Sanitary fixtures and sanitary appliances must be provided with hot water when intended to be used for

- a. utensil washing; and
- b. personal washing, showering, or bathing.