

Class 1 VCBC Shower Trays

Product Disclosure Information Self-Assessment

Version: V280723

Product name	VCBC Shower Trays
Product line	VCBC shower trays are part of the VCBC range by Bath Co.
Product identifier	Clear 6, Quadrant, Lucca, Central

Product description

VCBC shower trays are acrylic shower slimline shower trays designed to laid directly onto the floor surface. They are designed to be used with VCBC shower enclosures (see separate information sheet). They can be used as for 2 sided or 3 sided (alcove) showers where appropriate upstands have been fitted.

The height on the trays is 35mm with width and length ranging from 760 to 1800mm. The height of the upstand side is 55 to 75mm.

VCBC showers trays need to be installed with the easy clean waste provided.

VCBC shower trays are intended to be used with water temperatures from 10-55 degrees celcius.

Relevant building code clauses

B2 Durability - B2.3.1 (c)

F2 Hazardous building materials - F2.3.1

G1 Personal Hygiene - G1.3.2

G12 Water Supplies — G12.3.5

Contributions to compliance

Contributions to compliance

B2 Durability • B2.3.1 VCBC shower trays carry a 5 year domestic or 1 year non-domestic warranty.

F2 Hazardous building materials • F2.3.1 VCBC shower trays are safe when handled. There are no requirements for this product in order to comply with Acceptable Solution F2/AS1, First Edition Amendment 3,

2017.

G1 Personal Hygiene • G1.3.2 VCBC shower trays shall be installed to: facilitate sanitation, avoid harbouring dirt or germs, allow effective cleaning, discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and provide a healthy safe disposal system when non-water-borne disposal is used Sanitary fittings should be easy to locate and identify, with their operation easy to understand and suitable for both standing and seated users.

G12 For Water supplies G12, the prime building product objective is to ensure that the product used in water supply will not contaminate potable water either by way of material leaching into the water or cross connections and will not leak

Scope of use

VCBC acrylic shower trays are intended for domestic and commercial use. They are designed to enclose water to the shower area. They can be used with water temperatures up to 55 degrees celsius.

VCBC shower trays are designed to be used with VCBC shower enclosures and appropriate wall linings.

Conditions of use

VCBC shower trays must be installed in accordance with the instructions provided. We recommend these shower enclosures are installed by an authorised installer. Floor surfaces must be flat and free of movement.

This product is intended for domestic and commercial use.

This product is cleanable and impervious to to moisture — cleaning of the tray and waste shall be done in accordance with the manufacturer's cleaning instructions.

Supporting documentation

The following additional documentation supports the above statements:

Title (type)	Version	URL
Installation Instructions (Design, Installation, Maintenance)	V280723	https://www.bathco.co.nz/bathrooms/showers
Warranty Details (Warranty)	V280723	https://www.bathco.co.nz/warranties

Contact details

Manufacture location	Overseas
Legal and trading name of manufacturer	Bathroom Brands Group
Legal and trading name of importer	Bath Co.

Importer address for service	86 Wigram Road Christchurch 8025
Importer website	www.bathco.co.nz
Importer NZBN	9429041650790
Importer email	info@bathco.co.nz
Importer phone number	03 3430969

Warnings and bans

Is the building product/building product line subject to warning or ban under section 26 of the Building Act 2004?

No

Appendix

BPIR Ready selections

Category: Sanitary fixtures and appliances [legacy category]

	Yes	No
Suitable for Accessible facilities		×
Provision of hot water	×	

Building code performance clauses

All relevant building code performance clauses listed in this document:

B2 Durability

B2.3.1

Building elements must, with only normal maintenance, continue to satisfy the performance requirements of this code for the lesser of the *specified intended life* of the *building*, if stated, or:

(c) 5 years if:

- i. the *building elements* (including services, linings, renewable protective coatings, and *fixtures*) are easy to access and replace, and
- ii. failure of those building elements to comply with the *building code* would be easily detected during normal use of the *building*.

F2 Hazardous building materials

F2.3.1

The quantities of gas, liquid, radiation or solid particles emitted by materials used in the *construction* of *buildings*, shall not give rise to harmful concentrations at the surface of the material where the material is exposed, or in the atmosphere of any space.

G1 Personal Hygiene

G1.3.2

Sanitary fixtures shall be located, constructed and installed to:

- a. facilitate sanitation,
- b. avoid risk of food contamination,
- c. avoid harbouring dirt or germs,
- d. provide appropriate privacy,
- e. avoid affecting occupants of adjacent spaces from the presence of unpleasant odours, accumulation of offensive matter, or other source of annoyance,
- f. allow effective cleaning,
- g. discharge to a plumbing and drainage system as required by Clause G13 Foul water when water-borne disposal is used, and
- h. provide a healthy safe disposal system when non-water-borne disposal is used.

G12 Water Supplies

G12.3.5

Sanitary fixtures and sanitary appliances must be provided with hot water when intended to be used for

- a. utensil washing; and
- b. personal washing, showering, or bathing.