



Care & Maintenance

Bath Co InStyle wall panels are engineered for durability, moisture resistance, and low maintenance.

Proper care will ensure long-term appearance and performance.

1. Routine Cleaning

Frequency:

- As required based on environment (residential, commercial, wet areas)

Dry Cleaning:

- Use a soft microfibre cloth or duster to remove surface dust.
- Vacuum with a soft brush attachment if necessary.

Damp Cleaning:

- Wipe with a soft cloth or mop dampened with clean water.
- For general cleaning, use a pH-neutral mild detergent diluted in water.
- Rinse with clean water and wipe dry.

NB. Avoid excessive water pooling on joints or edges.

2. Stain Removal

CLEAN SPILLS IMMEDIATELY.

Stain Type and Recommended Method:

- Dirt / Mud: Damp cloth with mild detergent
- Grease / Oil: Diluted neutral cleaner
- Marker / Ink: Isopropyl alcohol (70%) lightly applied
- Soap Scum: Diluted vinegar solution (rinse immediately)

NB. Always test cleaning agents in an inconspicuous area first.

3. Cleaning Products to Avoid

Do NOT use:

- Abrasive pads or steel wool
- Strong alkaline or acidic cleaners
- Solvent-based cleaners (acetone, thinner, MEK)
- Bleach in high concentration
- Steam cleaners (unless specifically approved by manufacturer)
- Concentrated citrus cleaning products

NB. These will damage the surface wear layer or decorative film.

4. Moisture & Wet Area Care

InStyle wall panels are water-resistant; however:

- Ensure all joints are properly sealed during installation.
- Avoid prolonged water pooling.
- Avoid prolonged water exposure at cut edges.
- Maintain silicone seals around corners and fixtures.
- Repair damaged sealants promptly.
- Ensure good bathroom ventilation.

5. Impact & Surface Protection

- Avoid sharp objects impacting the surface.
- Do not drag heavy fixtures across the panel.
- Use protective pads behind mounted shelves and accessories.
- Do not drill or fix heavy items without proper support behind panels.

6. Temperature & Environment

- Suitable operating temperature: 0°C – 60°C.
- Avoid prolonged exposure to direct high heat (>60°C).
- Do not install near open flames or unshielded heat sources.
- This product is specifically designed for indoor use only, and prolonged exposure to direct sunlight should be avoided to preserve its appearance. Some slight fading or colour change may be experienced over the course of time when exposed to direct sunlight.

7. Periodic Inspection

Inspect every 6–12 months for:

- Loose panels
- Sealant deterioration
- Surface damage
- Joint movement

8. Repair & Replacement

- Replace damaged panels promptly to maintain performance and appearance.
- Damaged panels should be replaced by qualified installers.
- Do not attempt to remove interlocking panels without proper tools.

9. Warranty Preservation

- Follow manufacturer's installation guidelines.
- Use recommended adhesives and sealants.
- Avoid unauthorized modifications.
- Keep purchase and installation records.

Expected Service Life

- InStyle wall panels come with a 10-year conditional warranty. **See next page for full details.**



Warranty

InStyle Wall Panels are covered by a 10-year conditional warranty from the date of purchase, subject to the following terms and conditions.

This warranty is valid only where the product has been installed in strict accordance with the official InStyle Wall Panel installation instructions. The panels must be used on vertical internal surfaces only and are not suitable for external applications.

The product must not be installed within 1 metre of an open flame heat source and must not be exposed to water temperatures exceeding 60°C. Installation must be carried out using a compatible adhesive, specifically a modified silicone (MS) polymer-based adhesive, applied to a suitable substrate such as water-resistant plasterboard.

Failure to use an appropriate substrate, adhesive system, or installation method will void this warranty.

Some slight fading may occur over time when the product is exposed to direct sunlight.

This warranty is also conditional upon proper care and maintenance of the product in accordance with the InStyle Wall Panel Care & Maintenance Guide available [here](#).

This warranty is non-transferable and will not extend to any subsequent owners in the event of a property sale or ownership change.

This warranty does not cover any costs or losses associated with the removal, reinstallation, or replacement of the product, including labour or associated materials.

For commercial installations and short-term rental properties, a reduced warranty period of 1 year from the date of purchase applies.